

Multi Purpose Adhesive

Two Component Polyurethane Adhesive For Synthetic Sports Surfaces

INTRODUCTION

Sport-Fix Multi Purpose Adhesive is a two component polyurethane based adhesive system primarily designed for bonding, sand filled artificial grass carpets to our special seam jointing tapes to produce a strong invisible joint along the carpet joins.

FEATURES

- Solvent free non-flammable adhesive.
- Structured non-slumping consistency.
- Fast cure time.
- Versatile over 5 - 30 °C.
- Bonds generally far stronger than the materials used.
- Coloured green for low visibility on artificial grass.
- Tolerates use in damp weather conditions.

METHOD OF USE

IMPORTANT: Before embarking on any work involving Sport-Fix Multi Purpose Adhesive the Health and Safety Data Sheet should be carefully studied by those carrying out the work.

MIXING PROCEDURE

Sport-Fix Multi Purpose is mixed thoroughly with the Hardener Additive at a ratio of 10:1 by weight by first adding the hardener component to the adhesive component in the plastic tub.

Mixing in all cases should be carried out thoroughly by using a mechanical stirrer, for example a powerful drill with a suitable mixing head.

Poorly mixed adhesive does not cure correctly and remains soft. It is therefore essential that mixing of the two components is complete particularly around the edge and the bottom of the tub.

APPLICATION METHODS

Before use, individual substrates should be evaluated for bonding performance prior to any large-scale application.

The mixed adhesive should never be applied onto wet substrates as this interferes with the curing system and will result in inferior bonds. However Multi Purpose Adhesive is tolerant to use in damp weather conditions.

SEAM BONDING THE EDGES OF SAND FILLED SYNTHETIC GRASS

The mixed Adhesive is poured from the tub directly down the centre of the tape, or into a suitable application machine. The Adhesive is then spread by notched trowel (this allows the adhesive to stand up in ridges) across a width of 250 mm, leaving a 25 mm strip uncoated at each edge of the Tape.

Sport-Fix Multi Purpose is suitable for bonding sand filled synthetic grass to geo-textile tapes and a mixed set of 11.0 kg will bond down a seam length of up to 25 metres. It is important that sufficient adhesive is applied to transfer onto the carpet back when this is pressed into position and should effectively fill the gaps between the stitches. Therefore coverage can be down to 15 m per set on some types of the very long pile carpet.

The seam can be lightly rolled after making the joint and subsequently re-rolled when the adhesive is setting to a high viscosity mastic appearance (normally 1 - 2 hours).

Another method commonly used is to hold the seams tight by weighting the carpet with dry sand until the adhesive has cured. The adhesive will normally partially cure in 1 - 2 hours at average spring/autumn temperatures, but this time can be considerably extended at lower temperatures.

PRODUCT CHARACTERISTICS

Colour & Form:	Grass-green paste.		
Characteristics:	2 component Polyurethane-reaction adhesive for outdoor use.		
Specific Gravity:	1480 g/litre.		
Viscosity:	Thixotropic.		
Solids:	100%.		
Application:	Notched trowel or by special machine for applying to Seaming Tape.		
Open/Cure Time:	Ambient Temperature@C	Open Time	Cure Time
	5	4 hours	24 hours
	10	2 hours	12 hours
	20	1 hours	4 hours
	30	30 minutes	2 hours
	Do not use if risk of ground frost before completion of setting time.		
Coverage:	2000 g/m ² for seam jointing.		
Setting Time:	Approximately 1 - 24 hours depending on ambient temperature.		
Cure Time:	Final strength after 4 days.		
Cleaning:	Hot water plus detergent will remove (wet) adhesive from hands and tools. Cured adhesive is solvent resistant and is removable only by mechanical means.		
Film Resistance:	Water-resistant.		
Packaging	12 kg, 10 kg or 5 kg plastic tub - Adhesive. 1.2 kg, 1 kg or 0.5 kg metal tin - Hardener.		
Storage:	Keep containers tightly sealed between 5 °C-10		
Shelf Life:	12 months for both Adhesive and Hardener.		
Warning:	When working with hardener, the warning and safety precautions on the containers should be observed. EnviroStik Hardener is a 100% liquid isocyanate. Avoid contact with skin. Wear protective gloves.		

HEALTH & SAFETY

Before embarking on any work ensure you are supplied with the relevant Safety Data Sheet and have read carefully the following information.

- 1) The hazard label on the container (complying with Chip 3 Regs 2002 & CDG/CPL Regs).
- 2) The As Good As Grass Material Safety Data Sheet for Multi Purpose Adhesive.

This leaflet is for general guidance only and may contain inappropriate information under particular conditions of use. The company cannot accept any responsibility for loss or damage that may result from the use of this information, due to the possibility of variations of processing or working conditions and of workmanship outside our control. Users are advised to confirm the suitability of this product by their own tests.